

Gear-Ring Type Pipe Coupling 	O.D	Range	PN/WP
	(mm)	Min-max(mm)	(bar)
	21.7	21 — 23	16/32
	44.5	44 — 45.1	16/32
	79.9	78.8 — 80.8	14/28
	168	166 — 170	12/24
	273	271 — 275	8/16
Folding Type Pipe Repair Clamp 	O.D	Range	WP
	(mm)	Min-max(mm)	(bar)
	18	17 — 19	32
	63	62.2 — 63.9	32
	76.1	75 — 78	28
	159	157 — 161	24
	200	198.2 — 201.5	16
Double-Selection Pipe Repair Coupling 	O.D	Range	WP
	(mm)	Min-max(mm)	(bar)
	42	42 — 44	32
	57	56.3 — 57.7	32
	108	106 — 110	28
	140	137 — 143	28
	165.2	163.3 — 166.7	24
Non-Metal Pipe Coupling 	O.D	Range	WP
	(mm)	Min-max(mm)	(bar)
	63	62 — 64	20
	160	158 — 162	20
	200	198 — 203	16
	355	351 — 357	16
	500	497 — 503	12
Flexible Multi-Function Pipe Coupling 	O.D	Range	WP
	(mm)	Min-max(mm)	(Mpa)
	80	88 — 103	1.6
	100	108 — 132	1.6
	150	158 — 182	1.6
	200	214 — 238	1.6
	225	242 — 269	1.6
	300	310 — 356	1.6